

# **Features**

- Measuring SpO2, Pulse Rate and Temperature(optional)
- 3.5 inch TFT display of PI%, plethysmograph and pulse bar
- · Adult, pediatric and neonate measurement
- Lithium battery up to 18 hours
- 500 hours SpO2 data storage
- PC software for data upload



# **Technical Specifications**

# SpO<sub>2</sub>

Technique:	Dual-wavelength LED
Display range:	0%~100%
Measuring accuracy:	±3%(range from 70% to 100%)

#### **Pulse Rate**

Measuring range:	30~250bpm	
Measuring accuracy:	± 2bpm or ±2%	

# Temperature(option)

	,
Measuring range:	<b>32</b> ℃ <b>~43</b> ℃
Measuring accuracy:	± 0.2 °C
Measuring time:	≤ 5 seconds
Measuring probe:	Infrared ear probe

#### **Perfusion Index**

PI display range:	0.2%~20%	
r i dispiay i alige.	U.Z/6 ZU/6	

## **Measuring Mode**

Continuous or Spot check

# **Data Storage**

Up to 500 hours

# Display

3.5" color TFT display

#### **Power Supply**

2000mAh lithium battery

# Charging

Charging stand or USB cable

# **Dimension**

158mm x 73mm x 25mm

# Net Weight

230g

# **Data Upload**

USB cable or wireless

#### **Operating Environment**

Operating Temperature: 5 °C ~40 °C Operating Humidity: 15%-93%



Adult clip sensor



Pediatric soft sensor



Adult soft sensor



Neonate wrap sensor



Pediatric clip sensor



Infrared ear thermometer







**◎ C €**<sub>0123</sub> FDA 510(k)

#### Shenzhen Creative Industry Co., Ltd.

2/F, Block 3, Nanyou Tian'an Industry Town, 518054 Shenzhen, GD, P.R. China Tel:+86 755 26433514 Fax: +86 755 26430930 www.creative-sz.com info@creative-sz.com